



PIN 1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24
PIN 1A	1J	2COL	2H	2A	2J	3COL	3H	3A	3J	4COL	4H	4A	4J	5COL	5H	5A	5J	6COL	6H	6A	6J	7H	7G
PIN 1B	1K	2F	2G	2B	2K	3F	3G	3B	3K	4F	4G	4B	4K	5F	5G	5B	5K	6F	6G	6B	6K	7F	7G
PIN 1C	1M	2E	2Q	2C	2M	3E	3Q	3C	3M	4E	4Q	4C	4M	5E	5Q	5C	5M	6E	6Q	6C	6M	7E	7Q
PIN 1D	1N	1DP	2P	2D	2N	2DP	3P	3D	3N	3DP	4P	4D	4N	4DP	5P	5D	5N	5DP	6P	6D	6N	6DP	7P
PIN 25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44	45	46	47	48
PIN 7A	7J	11D	11DP	10D	10CDL	10DP	9D	8DP	8D	AD	B0	P7			P6	PL	A1	PLUS	1H			CM3	
PIN 7B	7K	11C	11E	10C	10E	10F	9C	9E	9C	8C	BE	AR	B1	P8		P5	P0	1F	1G			CM2	
PIN 7C	7M	11G	11F	10G	10F	9B	9G	8B	8G	AU	B2	P9			P4	P1	A3	1E	1Q			CM1	
PIN 7D	7N	11B	11A	10B	10A	9A	9F	8A	8F	AL	BRB1	PR			P3	P2	A4	MINUS	1P			CM0	

NOTE:

- 1 DISPLAY TYPE: TN
- 2 POLARIZER MODE: TRANSPARENTIVE/POSITIVE
- 3 VIEWING DIRECTION: 6:00
- 4 DRIVE METHOD: 1/ 4DUTY, 1/ 3BIAS
- 5 OPERATING VOLTAGE: 2.7V TD 3.6V
- 6 OPERATING TEMP.: -20 °C ~ 50 °C
- 7 STORAGE TEMP.: -20 °C ~ 60 °C